1. Incident Name	2. Operational Period to be covered by IAP (Date/Time) CG IAP COVER SHEET						
Dominguez Channel Mystery Oil Spill	From: 0600 2/11/11 To	: 0600 3/4/11	COVER SHEET				
3. Approved by Incident Commander(s):	. 1						
ORG NAME	Terrillian - 2/10	1.,					
US EPA Marty Powell / Jason Musantel	1880003118	[ <u> </u>					
DFG Sau Garcia #659 / Bryan Gollhofer		/// // #2931					
LAWPD Howard Wong	Worz 110/	11 #2931	6				
RP/ACTA Elaine Silvestro							
	NT ACTION PLAN  slow are included in this Incident Action Plan	:					
ICS 202-CG (Response Objectives)							
ICS 203-CG (Organization List) – OR – ICS 20	7-CG (Organization Chart)						
ICS 204-CGs (Assignment Lists) One Copy each of any ICS 204-CG attachmen	:s:						
ICS 205-CG (Communications Plan)		1	managan				
ICS 206-CG (Medical Plan)							
ICS 208-CG (Site Safety Plan) or Note SSP Lo	cation						
Weather forecast / Tides/Currents							
Other Attachments							
Incident Phone List							
Waste Segregation and Qualification Plan							
⊠ msds							
Emergency Rain Event Notification							
4. Prepared by:	Date/Time		nacenne phonon (1907) de la vivie de mandré (1959) de la vivie de				
J. Pantoia	2/10/11 0800						

1. Incident Name	2. Operational Period (Date/Time)	T INCIDENT OD JEGTIVES						
Dominguez Channel Mystery Oil Spill	From: 2-11-11 0600 To: 3-4-11 0600	INCIDENT OBJECTIVES ICS 202-CG						
Objective(s)     SAFETY: Ensure the safety of all response personnel, facility employees, and public. See site safety plans for specifics								
- ISOLATION AND DENY ENTRY: Keep all non response personnel out of response areas.								
- NOTIFICATIONS: Notify proper authorities of any significant changes in spill situations.								

- ID AND HAZARD ASSESSMENT: See site safety plan.
- ACTION PLANNING: Maintain containment and remove oil at source, pump station and retention basin.
- CONTAINMENT AND CONTROL: Investigate possible sources and control when found.
- PROTECTIVE ACTIONS: Continually assess downstream impacts and potential protective and recovery options (Marina's).
- DECONTAMINATION AND CLEANUP: Ensure proper decontamination of personnel and equipment.
- DISPOSAL: Dispose of all recovered as waste as law requires. Ensure that attached Waste Segregation Plan is followed.
- DOCUMENTATION: Ensure proper documentation of all response activities, waste and segregation, and costs associated.

### 4. Operational Period Command Emphasis (Safety Message, Priorities, Key Decisions/Directions)

- SHELL SOURCE AREA:
  - -Obtain Right-of Entry (ACTA).
  - -Mobilize equipment (NRC).
  - -Continue recovery of surface product (NRC).
  - -Contain and segregate waste; keep separate from other wastes (NRC).
- RR ROW OUTFALL RECOVERY:
  - -Mobilized equipment (NRC).
  - -Maintain established temporary sand bag drain and pond.
  - -Continue skimming and recovery efforts to minimze downstream impacts to pump station.
  - -Assess cleanup issues to implement once source has been isolated.
  - -During a rain event initiate call out list and staff as necessary.
- SOURCE INVESTIGATION
  - -Work in conjunction with agencies to determine source.
  - -Once source is found, work with responsible party(ies) to revise IAP.
  - -Additional ICS 204's as needed for new projects to identify source.
- CITY PUMP STATION
  - -Continue recovery of surface water within vault.
  - -Pump down station as needed to reduce water level and reduce possibility of flooding. Portable sump pump as a possibility. -Continue to assess.

#### Approved Site Safety Plan Located at:

J. Pantoja

Date/Time 2/10/11 0800

#### 1. Incident Name

Dominguez Channel Mystery Oil Spill

#### 2. Prepared by: (name) Sau Garcia

Date: 02/10/2011

Time: 1430


INCIDENT BRIEFING ICS 201-CG

3. Map/Sketch (include sketch, showing the total area of operations, the incident site/area, overflight results, trajectories, impacted shorelines, or other graphics depicting situational and response status)




#### 4. Current Situation:

- Source of crude oil is unknown and is an on going investigation
- Source is believed to be traveling through the ballast of the Alameda Corridor
- Containment and recovery are currently in place at Shell Source Area, Right of Way Trench, and at the City Outfall Pump.



Incident Name:     Dominguez Mystery Oil Spill	4. Operational Period: From: 0600 2/11/11	1 11 11 11							
5. Incident Medical Aid Station									
Medical Aid Stations						ramedics			
Medical Aid Stations		Location			Yes	No			
6. Transportation									
	A. Ambulance	Services			Do				
Name	Address		Phone		Yes	ramedics No			
South County Medical Transport	228 E. Pacific Coast Highway, Long Be	each	562-599-0659		X				
	B. Incident Am	bulances				4 - 1			
7. Hospitals  Name  Pacific Hospital of Long Beach	Address 2776 Pacific Ave. Long Beach 90806	Travel Ti	me Phone 562-997-2000	Helipa Yes	d No X	Burn Center Yes No X			
8. Medical Emergency Procedure	S								
9. Prepared by (Medical Unit Lead									



#### Your National Weather Service forecast

# 3 Miles ESE Lomita CA



Enter Your "City, ST" or zip code

Go

BOOKMARK ■ □□□...

NWS Los Angeles/Oxnard, CA **Point Forecast:** 3 Miles ESE Lomita CA
33.78°N 118.27°W (Elev. 16 ft)

Last Update: 2:21 pm PST Feb 9, 2011 Forecast Valid: 5pm PST Feb 9, 2011-6pm PST Feb 16, 2011

Mobile Weather Information | En Español

Sunday

Hi 70 °F

#### Forecast at a Glance



Lo 49 °F

**Tonight** 



Hi 73 °F

Thursday






Hi 75 °F



Saturday

Hi 74 °F



Lo 50 °F

ostly Sunny



Cloudy Lo 50 °F

[Move Down]

3 Day History:

Sunday

**Detailed 7-day Forecast** 

Hazardous weather condition(s):

#### **Hazardous Weather Outlook**

**Tonight:** Clear, with a low around 49. North northwest wind 5 to 10 mph becoming east northeast.

Thursday: Sunny, with a high near 73. East northeast wind around 5 mph becoming calm.

**Thursday Night:** Clear, with a low around 48. North northwest wind around 5 mph.

**Friday:** Sunny, with a high near 75. Calm wind becoming northeast around 5 mph.

Friday Night: Clear, with a low around 50. West northwest wind between 5 and 10 mph becoming calm.

Saturday: Sunny, with a high near 74.

Saturday Night: Mostly clear, with a low around 50.

Sunday: Sunny, with a high near 70.

Sunday Night: Partly cloudy, with a low around 50.

Monday: Mostly sunny, with a high near 66.

Monday Night: Mostly cloudy, with a low around 50.

Tuesday: A slight chance of rain. Partly sunny, with a high near 64.

Tuesday Night: A slight chance of rain. Mostly cloudy, with a low around 50.

Wednesday: A slight chance of rain. Mostly cloudy, with a high near 60.

# Current Conditions Torrance, Zamperini Field Airport

Torrance, Zamperini Field Airpor Last Update on 09 Feb 15:47 PST

 Fair
 Humidity:
 23 %

 Wind Speed:
 WSW 9 MPH


 Barometer:
 30.04 in (N/A mb)

 70°F
 Dewpoint:
 30°F (-1°C)

 (21°C)
 Visibility:
 20.00 Miles

More Local Wx:

# Radar and Satellite Images



---Requested Location Forecast Area Lat/Lon: 33.78°N 118.27°W Elevation: 16 ft Additional Forecasts & Inform Zone Area Forecast for Los Angeles County Coast including Downtown Los Angeles, CA Forecast Discussion Printable Forecast Text Only Forecast Hourly Weather Graph Tabular Forecast Quick Forecast International System of Units About Point Forecasts Observation Map (Los Observation Map (Regional) Angeles) **Experimental Graphical** Warnings Forecasts Quantitative Precipitation Climatology Forecast Forecast Weather Table Interface Webmaster www.weather.gov Back to Previous Page National Weather Service: Privacy Policy Los Angeles/Oxnard, CA Disclaimer Credits

# February - Long Beach, Terminal Island

Date	Day	Time		Heig	ht	Time		Heig	ht	Time		Heigh	ıt	Time		Heig	ht	Time	Height
02/01/2011	Tue	01:39AM	LST	1.8	L	07:46AM	LST	6.1	H	02:48PM	LST	-0.9	L	09:11PM	LST	4.1	H		
02/02/2011	Wed	02:16AM	LST	1.6	L	08:21AM	LST	6.0	H	03:16PM	LST	-0.8	L	09:36PM	LST	4.3	Υ·I		
02/03/2011	Thu	02:51AM	LST	1.5	L	08:54AM	LST	5.8	Н	03:43PM	LST	-0.6	L	10:01PM	LST	4.3	Н		
02/04/2011	Fri	03:25AM	LST	1.4	$I_{t}$	09:25AM	LST	5.5	H	04:07PM	LST	-0.3	T.,	10:25PM	LST	4.4	H		
02/05/2011	Sat	04:00AM	LST	1.4	T.	09:56AM	LST	5.0	H	04:30PM	LST	0.1	L	10:51PM	LST	4.5	Н		
02/06/2011	Sun	04:37AM	LST	1.4	L	10:28AM	LST	4.5	H	04:53PM	LST	0.5	L.	11:17PM	LST	4.5	H		
02/07/2011	Mon	05:19AM	LST	1.5	I.t	11:02AM	LST	3.9	H	05:14PM	LST	0.9	L	11:47PM	LST	4.5	H		
02/08/2011	Tue	06:10AM	LST	1.6	L	11:43AM	LST	3.3	Н	05:34PM	LST	1.4	T.s						
02/09/2011	Wed	12:22AM	LST	4.4	H	07:21AM	LST	1.6	L	12:43 PM	LST	2.7	Н	05:51PM	LST	1.8	L		
02/10/2011	Thu	01:08AM	$_{\rm LST}$	4.4	H	09:06AM	$_{\rm LST}$	1.5	L	03:15PM	LST	2.3	Н	05:58PM	LST	2.2	L		
02/11/2011	Fri	02:14AM	LST	4.4	H	10:50AM	LST	1.1	L										
02/12/2011	Sat	03:33AM	LST	4.6	H	11:50AM	LST	0.5	L	07:05PM	LST	2.9	H	10:00PM	LST	2.7	L		
02/13/2011	Sun	04:43AM	LST	5.0	Н	12:32PM	LST	-0.1	L,	07:20FM	LST	3.2	H	11:21PM	LST	2.5	L		
02/14/2011	Mon	05:40AM	LST	5.6	H	01:07PM	LST	-0.6	L	07:42PM	LST	3.6	Н						
02/15/2011	Tue	12:17AM	LST	2.1	L	06:28AM	LST	5.0	H	01:41PM	LST	-1.0	L	08:06PM	LST	4.0	H		
02/16/2011	Wed	01:05AM	LST	1.6	L	07:14AM	LST	6.4	H	02:14PM	LST	-1.2	L	08:34PM	LST	4.4	H		
02/17/2011						07:58AM	LST	6.5	H	02:47PM	LST	~1.3	L	09:04PM	LST	4.8	H		
02/18/2011	Fri	02:37AM	LST	0.6	L	08:43AM	$_{\rm LST}$	6.4	H	03:21PM	LST	-1.1	L	09:37PM	LST	5.2	H		
02/19/2011	Sat	03:25AM	LST	0.3	L	09:29AM	LST	6.0	H	03:55PM	LST	-0.7	L	10:12PM	LST	5.5	H		
02/20/2011	Sun	04:16AM	LST	0.1	$\Gamma$	10:17AM	LST	5.4	H	04:30PM	LST	-0.2	L	10:50PM	LST	5.7	H		
02/21/2011						11:10AM	LST	4.5	H	05:05PM	LST	0.4	$\Gamma$	11:32PM	LST	5.7	H		
02/22/2011									H	05:44PM	LST	1.1	Ţ.						
02/23/2011										01:39PM									
02/24/2011							LST	0.4	L	03:51PM	LST	2.8	H	07:39PM	LST	2.3	L		
02/25/2011										05:47PM	LST	3.1	H	09:37PM	LST	2.6	L		
02/26/2011										06:44PM	LST	3.5	H	11:13PM	LST	2.4	$\mathcal{L}_{t}$		
02/27/2011										07:20PM									
02/28/2011	Mon	12:15AM	LST	2.1	1.,	06:16AM	LST	5.4	H	01:19PM .	LST	-0.5	L	D7:48PM	LST	4.0	H		
All times are lie	sted is	a Local Star	ndard	Time	ICTY	or Local F	nilve	ht Tim	0/11	TV (when a	molic	able) /	SILE	olahta ara l	in foot	rafar	onee	dto Moon L	aurar Laur Mahan

All times are listed in Local Standard Time(LST) or, Local Daylight Time (LDT) (when applicable). All heights are in feet referenced to Mean Lower Low Water (MLLW).

# March - Long Beach, Terminal Island

Date Day Ti	ime	Height	Time	Height	Time	Height	Time	Height	Time Height
03/01/2011 Tue 12				5.5 H	01:51PM LST	-0.5 L	08:12PM LST	4.2 H	
03/02/2011 Wed 0:									
03/03/2011 Thu 03	2:08AM LST	1.1 L	08:10AM LST	5.4 H	02:43PM LST	-0.3 L	08:55PM LST	4.6 H	
03/04/2011 Fri 02									
03/05/2011 Sat 03								4.8 H	
03/06/2011 Sun 0	3:42AM LST	0.6 L	09:42AM LST	4.5 B	03:47PM LST	0.6 L	09:59PM LST	4.9 H	
03/07/2011 Mon 0	4:17AM LST	0.6 L	10:15AM LST	4.1 H	04:07PM LST	0.9 L	10:23PM LST	4.9 H	
03/08/2011 Tue 0/					04:26PM LST		10:49PM LST		
03/09/2011 Wed 0:	5:39AM LST	0.8 L	11:35AM LST	3.1 H	04:43PM LST	1.7 L	11:21PM LST	4.7 H	
03/10/2011 Thu 0	6:37AM LST	1.0 L	12:40PM LST	2.6 H	04:56PM LST	2.1 L			
03/11/2011 Fri 1:	2:02AM LST	4.6 H	08:03AM LST	1.0 L					
03/12/2011 Sat 0:									
03/13/2011 Sun 0							10:51PM LDT	2.8 L	
03/14/2011 Mon 0	5:08AM LDT	4.7 H	12:49PM LDT						
03/15/2011 Tue 1:							08:00PM LDT		
03/16/2011 Wed 0	1:09AM LDT	1.7 L	07:10AM LDT	5.6 H	02:03PM LDT	-0.7 L	08:25PM LDT	4.4 H	
03/17/2011 Thu 0									
03/18/2011 Fri 0									
03/19/2011 Sat 0	3:30AM LDT	-0.3 L	09:36AM LDT	5.7 H	03:46PM LDT	-0.4 L	09:58PM LDT		
03/20/2011 Sun 0	4:17AM LDT	-0.6 L	10:24AM LDT	5.4 H	04:20PM LDT	0.0 L	10:34PM LDT	6.2 H	
03/21/2011 Mon 0							11:12PM LDT		
03/22/2011 Tue 0							11:55PM LDT	6.0 H	
03/23/2011 Wed 0									
03/24/2011 Thu 1							07:05PM LDT		
03/25/2011 Fri 0	1:44AM LDT	5.0 H	09:37AM LDT	0.1 1	04:50PM LDT	3.1 H	08:34PM LDT	2.7 L	
03/26/2011 Sat 0							10:44PM LDT	2.7 L	
03/27/2011 Sun 0					07:09PM LDT				
03/28/2011 Mon 1	2:13AM LDT	2.3 L	06:01AM LDT	4.5 H	01:03PM LDT	0.0 L	07:42PM LDT	4.0 H	
03/29/2011 Tue 0									
03/30/2011 Wed 0	1:51AM LDT	1.4 L	07:44AM LDT	4.7 H	02:12PM LDT	' 0.1 L	08:30BW TDL	4.5 H	
03/31/2011 Thu 0									ad to Mann Lower Low Water

All times are listed in Local Standard Time(LST) or, Local Daylight Time (LDT) (when applicable). All heights are in feet referenced to Mean Lower Low Water (MLLW).

Dominguoz Channol Myctory Oil Snill				. Operational Period (Date/Time)  Assignment I  rom: 2/11/11 0600 To: 3/4/11 0600 ICS 204-					
3. Branch	.h	T 4 Dîvi	From: 2/- sion/Group/		300	Го: 3/4/11 0600	103 204	1-UG	
Recovery Group		Right	of Way Tren	och					
5. Operations Personnel	Na	ime	Affil	iation		Contact # (s)			
Operations Section Chief: <u>St</u>	eve Pederson		City of L	os Angele	es	213 - 725 - 630	3		
Branch Director: <u>El</u>	aine Silvetro		ACTA			310 - 650 - 335	9		
Division/Group Supervisor/STAM:	NRC Environ	mental Service	es, Inc.		***************************************				
6. Resources Assigned			tikki in a saata saa	"X"		204a attachment with ac	lditional instruction	ons	
Strike Team/Task Force/Resource Identifier	Leader		Contact Info	). #	# Of Persons	Reporting Info/	Notes/Remarks	•	
Senior Project Manager	Asher Grimes	s 310 -	629 - 2760		1				
Project Accountant					1				
Project Managert	Mike Sica	310 -	628 - 0725		1				
Field Supervisor					2				
Vacuum Truck Driver					2	to be mobilized			
Technician					12	to be mobilized			
4 pickup trucks						to be mobilized			
2 gear trucks						to be mobilized			
ER Trailer						to be mobilized			
Incident command Trailer						to be mobilized			
1 Tractor						to be mobilized			
7. Work Assignments Maintain walls with lessons learned in mind. Widen outfall to allow more retention time. Recover liquids in vacuum truck.  8. Special Instructions Build containment with permanency in mind. Keep sandbags segregated from Shell site Read, understand, and follow site safety plan Do not attempt to captured or approach oiled / injured wild life. Notify an on - site DFG personnel or a member of the Unified Command Report all oiled wildlife to Cory Kong @ 562 - 477 - 7081 Refer all media guestions and concerns to martin Powell @ 562 - 760 - 7028.									
9. Communications (radio and/or	phone contac	t numbers nec	eded for this	s assignm	nent)		Takat 1988-kilok (1989-kilok erranere anga angang anganasa sa	Barrier of the second	
Name/Function	-	dio: Freq./Syste		-		Cell/Pager			
Emergency Communications									
Medical	TOTAL SECTION OF THE PARTY OF T	cuation			Other				
<b>10. Prepared by:</b> J. Pantoja 0800	<b>Date/Time</b> 2/10/11	11. Reviewed	d by (PSC):	Dat	e/Time	12. Reviewed by (OSC	C): Date/1	Гime	

				2. Operational Period (Date/Time)  Assignment List						
Dominguez Channel Mystery Oil S	pill		From: 2/		300	Го: 3/4/11 0600	ĬCS 204	1-CG		
3. Branch Recovery Group		4. Divi	sion/Group of Way Trer	/Staging nch						
5. Operations Personnel	Na	ne	Affil	iation		Contact # (s)				
Operations Section Chief: Ste	ve Pederson		City of L	os Angele	es	213 - 725 - 630	3			
Branch Director: <u>Ela</u>			ACTA			310 - 650 - 3359	)			
Division/Group Supervisor/STAM:	NRC Envi	onmental Serv	rices, Inc.		NATIONAL CONTRACTOR OF THE PROPERTY OF THE PRO			-		
6. Resources Assigned				"X"		204a attachment with ac	lditio <b>n</b> al instruction	ons		
Strike Team/Task Force/Resource Identifier	Leader		Contact Info	). #	# Of Perso <b>n</b> s	Reporting Info/	Notes/Remarks	<b>\</b>		
1 Vacuum trailer					1	to be mobilized				
1 generator					1	Pre staged				
1 Skimmer					1	Pre staged				
1 Air Compressor					2	Pre staged				
2 3" pumps					2	Pre staged				
12 25" hose					12	Pre staged				
2 light towers						Pre staged				
2 - 4" trash pumps			***************************************	-		Pre staged				
8" sorbent boom				ŧ		Pre staged				
sorbent pads						Pre staged				
visqueen						Pre staged				
7. Work Assignments								elemment co-c-c-c		
Maintain walls with lessons learned in	n mind. Widen	outfall to allow	more reten	tion time. I	Recover li	quids in vacuum truck.		NOW ON THE SECOND		
8. Special Instructions Build containment with permanency in mind. Keep sandbags segregated from Shell site.  - Read, understand, and follow site safety plan.  - Do not attempt to captured or approach oiled / injured wild life. Notify an on - site DFG personnel or a member of the Unified Command.  - Report all oiled wildlife to Cory Kong @ 562 - 477 - 7081.  - Refer all media questions and concerns to martin Powell @ 562 - 760 - 7028.										
9. Communications (radio and/or p		numbers nee o: Freq./Syste		•	nent)	<u>Cell/Pager</u>				
	************	***************************************								
Emergency Communications					٠					
Medical  10. Prepared by:	Eva Date/Time	uation 11. Reviewe	d by (PSC).	Dat	Other e/Time	12. Reviewed by (OSC	:): Date/1	Fimo		
J. Pantoja 0800	2/10/11		, (i oo).	Dat	i iiii G	However by (OSC	.,. Date/			

1. Incident Name	2. Ope	2. Operational Period (Date/Time)  Assignment Lis					
Dominguez Channel Mystery Oil Sp	llic	From:	2/11/11 06	00	To: 3/4/11 0600	ICS 204-CG	
3. Branch Recovery Group	TO CONTROL OF THE PROPERTY OF	4. Division/Gro Right of Way T			марилия (4 марин — том развительной применення в под образований применення в под образований применення в под		
5. Operations Personnel	Name	e #	Affiliation		Contact # (s)	1987-201-1987-1987-1987-1987-1987-1987-1987-198	
Operations Section Chief: Ste	ve Pederson	City	of Los Angeles	S	213 - 725 - 6308	8	
Branch Director: <u>Ela</u>		ACT			310 - 650 - 3359	9	
Division/Group Supervisor/STAM:	NRC Enviror	mental Services, Inc		75-111-16-16-16-16-16-16-16-16-16-16-16-16	T		
6. Resources Assigned			"X" i	MATERIAL PROPERTY OF THE PARTY	204a attachment with ac	Iditional instructions	
Strike Team/Task Force/Re <b>s</b> ource Identifier	Leader	Contact I	nfo. #	# Of Persons	Reporting Info/	Notes/Remarks	
Pressure washer					To be mobilized		
Skidsteer loader					To be mobilized		
2 Baker Tanks					Pre staged		
Rocket launcher					To be mobilized		
Roll off bins					To be mobilized		
					,		
				, , , , , , , , , , , , , , , , , , ,			
7. Work Assignments		CONTRACTOR AND ADDRESS AND ADD		<del>ar mananda an matan matan matan an</del>	et et el est		
Maintain walls with lessons learned in	ı mind. Widen οι	ıtfall to allow more ret	ention time. R	Recover li	quids in vacuum truck.		
8. Special Instructions Build containment with permanency ir - Read, understand, and follow site s - Do not attempt to captured or appro Report all oiled wildlife to Cory Kong Refer all media questions and conce	safety plan. Dach oiled / injure g @ 562 - 477 - erns to martin Po	ed wild life. Notify an - 7081. owell @ 562 - 760 - 7	on - site DFG	personn	el or a member of the Ur	nified Command.	
Communications (radio and/or p     Name/Function		umbers needed for to the street of the stree	-	ent)	Cell/Pager		
					<u>5511/1 agor</u>	***************************************	
· · · · · · · · · · · · · · · · · · ·					•		
Emergency Communications							
Medical		ation	**************************************	ALCOHOL: SHEET SHE			
<b>10. Prepared by:</b> J. Pantoja 0800	<b>Date/Time</b> 1 2/10/11	11. Reviewed by (PS	C): Date	/Time	12. Reviewed by (OSC	c): Date/Time	

ASSIGNMENT LIST ICS 204-CG (Rev 04/04)

1. Incident Name		2. Operationa	2. Operational Period (Date/Time)  Assignment List						
Dominguez Channel Myster	y Oil Spill	From: 2/11,	/11 0600 T	o: 3/4/11 0600	ICS 204-CG				
3. Branch		4. Division/Group/Stag							
Recovery Group		Shell Source Are	ea						
5. Operations Personnel	Name	Affiliation	1	Contact # (s)					
Operations Section Chief: _S	teve Pedersen	City of Los	Angeles	213-725-63	08				
Branch Director: $^{ ext{El}}$	aine Silvestr	o ACTA		310-650-33	59				
Division/Group Supervisor/STAM:	NRC Env	rironmental Servi	ces Inc.						
6. Resources Assigned	The second secon		"X" indicates	204a attachment with ad	ditional instructions				
Strike Team/Task Force/Resource Identifier	Leader	Contact Info. #	# Of Persons	Reporting Info/I	Notes/Remarks				
500 bbl baker tank									
1 vac truck operator									
1 tech				`					
1 tractor									
1 vacuum trailer									
					· 🗆				
		:							
					П				
7. Work Assignments									
Maintain walls with less	ons learned i	n mind. Widen out	fall to al	low more retenti	on time.				
Recover liquids in vacuu	m truck.								
-									
		MCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC		INVESTIGATION OF THE CONTRACT	Name to the control of the control o				
8. Special Instructions Build containment with pe	ermanency in m	aind Keen sandha	ag geareasi	ted from Shell s	ite				
-Read, understand, and for -Do not attempt to capture	ollow site saf	ety plan.	ga begregat	tifu on an aite	DEC nomenos				
or a member of the Unifi	.ed Command		ridille. No	otily an on-site	DrG bersonner				
-Report all oiled wildlif	e to Cory Kon	-	77 - 500 -						
-Refer all media questior	is and concern	s to Martin Powe	11 @ 562-76	50-7028					
9. Communications (radio and/or p	hone contact num	bers needed for this as	sianment)						
Name/Function		eg./System/Channel Ph	-	Cell/Pager	A				
Park									
					X				
Emergency Communications									
Medical	Evacuatio	garden out of the second of th	Other						
10. Prepared by: A. Wilson 2/10	<b>Date/Time</b>   <b>11. I</b>	Reviewed by (PSC):	Date/Time	12. Reviewed by (OSC	C): Date/Time				

ASSIGNMENT LIST ICS 204-CG (Rev 04/04)

1. Incident Name	2.	2. Operational Period (Date/Time)								
Dominguez Channel Mystery Oil S	pill	Fi	rom: 0600 2/1	1/11 -	Го: 0600 3/4/11	Assignment List ICS 204-CG				
3. Branch Recovery Group		4. Division City Outfa	n/Group/Stagin II Pump	g	and the second distribution of the second	Destinate destinates and appropriate the extension of the				
5. Operations Personnel	Name		Affiliation		Contact # (s)					
Operations Section Chief: Ste	ve Pedersen		City of Los	Anneles	213-725-6308					
Branch <b>D</b> irector: <u>Ela</u>			ACTA	Angeles	310-650-3359					
Division/Group Supervisor/STAM: Mil				onmental Se						
6. Resources Assigned			£1	'X" indicates	204a attachment with ac	Iditional instructions				
Strike Team/Task Force/Resource	Leader	Con	tact Info. #	# of Persons	Reporting Info/	Notes/Remarks				
1 Supervisor				2	ACTA					
6" pump						in the second				
Absorbent boom										
	······································									
			**************************************							
7. Work Assignments Continue utilizing pads and sorbent b Friday at 0800; 1500; 2400 and on Sa	7. Work Assignments Continue utilizing pads and sorbent boom to remove sheen and oil and maintain passive cleaning operations. Man the pump Monday thru Friday at 0800; 1500; 2400 and on Saturday and Sunday at 0800 and 2000.									
8. Special Instructions All discharge must be monitored. Working near water. Wear life jackets Read, understand, and follow site safety plan Do not attempt to capture or approach oiled/injured wildlife. Notify an on-site DFG personnel or a member of the Unified Command Report all oiled wildlife to Cory Kong @ 562-477-7081 - Refer all media questions and concerns to Martin Powell @ 562-760-7028										
9. Communications (radio and/or p Name/Function			•	,	0.170					
ivarile/Function	Hadio:	Freq./System/C	nannei	Phone	Cell/Pager					
				· · · · · · · · · · · · · · · · · · ·						
Emergency Communications			***************************************							
Medical	Evacua	tion		Other						
10. Prepared by		. Reviewed by	(PSC)	Date/Time	12. Reviewed by (OSC	Date/Time				

# Dominguez Channel Mystery Oil Spill Emergency Rain Event Notifications

 Steve McQuay, DWP Sanitation Supervisor, City of Los Angeles Pump Station Operator

24-Hour Notification: 213-300-3662

Alternates:

Howard Wong: 213-725-6313 Steven Pedersen: 213-725-6308

NRC Environmental

24-Hour Notification: 1-800-337-7455

Alternates:

Michael Sica: 310-628-0725 Jim Kiatos: 310-628-1211

• Randy Stuart, Balfour Beatty Rail for RR Crossing Access

24-Hour Notification: 310-863-0912

Mike Mejia for all TV events: 310-863-0860

Tesoro Tower/Shell Sump Valve Operation
 310-522-8665 (if no answer will roll over to cell phone for on-call person)

Steven Pedersen, LA City (Courtesy Call): 213-725-6308

Alternates:

Joe Fortaleza: 213-725-6304

Tri Tran: 213-725-6306

OSC Marty Powell, EPA: 562-760-7028

#### Waste Segregation and Quantification Plan

Date: January 14, 2011

Incident Name: Bouinguez Channel Mystery Oil Spill

Location Latitude: 33. 785010, Longitude: -118. 2372450

#### **OBJECTIVE**

To facilitate proper disposal and quantification of recovered pollutant generated from response and recovery operations associated with the incident named above.

#### WASTE STREAM SEPARATION

Recovered pollutant shall be separated by waste stream type and location where the waste was recovered. Pollutants recovered from Waters of the State shall be kept separate from pollutants recovered elsewhere.

Liquids: Liquids shall be held in secure tanks for gauging to determine oil content by DFG and Responsible Party representatives prior to disposal. In order to expedite cleanup and disposal, a direct assessment of the contents can be made, or a representative sample may be analyzed by the TSD Facility. Liquids recovered during flushing or steaming and Decontamination operations should be kept separate from recovered free floating oil.

Solids: Recovered pollutant held in solids will be placed onto roll-off bins or over-pack drums with tare weights. Solids shall be segregated as follows; sorbents, debris (oiled), soil, or PPE. Solids recovered from Waters of the State or adjacent shorelines shall be stored separate from those recovered elsewhere.

Vegetation/Wildlife: Vegetation and/or wildlife removed in the cleanup operation will be bagged and weighed separately.

#### QUANTIFICATION

Quantification of recovered pollutants will be conducted in accordance with California Code of Regulations Title 14, Section 877. The Responsible Party and the Department of Fish and Game may stipulate to the amount of oil spilled and/or recovered. The amount of recovered pollutant can be determined by visual assessment by DFG and responsible party or by lab analysis of samples taken in the presence of DFG and responsible party representatives.

#### FINAL DISPOSAL

When quantification is final, the waste may be disposed of in accordance with all Federal, State, and Local laws. A copy of the Hazardous Waste Manifest and associated documents shall be provided to the DFG as proof of disposal.

# INCIDENT NAME: Dominguez Channel Mystery oil Spill

The following table indicates the types of waste to segregate. Place a checkmark in the appropriate box for this incident. This plan should be included in the IAP.

Wa	ters of the S	tate of California				
Liquids		Solids				
Free Floating Product		Sorbent materials				
Flushing and/or Steam Cleaning		Vegetation / Sediment				
Decontamination		Impacted Wildlife				
	:	Oiled Trash & Debris				
deellassa middelissa oo oo ga aadaadda iirii iirii oo aadaa aa aada dhaa ayaa ayaa ahaa ahaa		PPE	A CONTRACTOR OF THE PROPERTY O			
in the second se		Response Materials				
	Non-Water	rs of the State	<u> </u>			
Liquids		Solids				
Recovered on property		Sorbent Boom/Pads				
Recovered off property		Vegetation / Soils	······································			
W/I 2ndry containment		Impacted Wildlife				
Product from Source	`	Oiled Trash & Debris	· ·			
Steam Cleaning		PPE	NA.			
Decontamination		Response Materials	·			
Comments:	ataliti ili anti anti anti anti anti anti anti ant	<u> </u>	<u> </u>			
	· · · · · · · · · · · · · · · · · · ·					
	takan manan manya kaominina dia kabana arawa					

Dominguez Channe		ational Period (Date / Time) 2/11/11 0600 To: 03/04/11 0600	COMMUNICATIONS LIST ICS 205A-CO
3. Basic Local Com	munications Information		
Agency	Name	Method(s) of contact (radio freque	ency, phone, pager, cell #(s), etc.)
US EPA	Jason Musante	213-479-2120	
US EPA	Martin Powell	562-760-7028	
CA DFG OSPR	Anastasia Norris	310-310-9917	
CA DFG OSPR	James Foto	562-598-4292	
LA WPD	Howard Wong	213-725-6313	
BBRI	Mike Mejia	310-863-0860	
Shell	Brett Bernstein	213-494-6598	
OLBI	Dean Persinger	562-624-3284	
OLBI	Charlie Waters	562-900-2347	
ACTA	Elaine Silvestro	310-650-3359	
ACTA	Jorge Pantoja	310-816-0460	
EPA START	Adam Smith	310-405-2393	
CA DFG OSPR	Bryan Gollhofer	562-708-7757	
CA DFG OSPR	Sau Garcia	562-843-2714	) :
LA WPD	Eric Lee	213-725-6313	· · · · · · · · · · · · · · · · · · ·
LA WPD	Gonzalo Barriga	213-725-8862	<u> </u>
CAL FIRE	Tom Williams	562-425-1902	₹ ×
CA DFG OSPR	Corey Kong	562-477-7081	
Tesoro	Pang Mueller	310-522-4976	
Tesoro	Emile Nour	310-522-6212	
Crimson	Tracy Wilkinson	562-346-4296	
Crimson	Mike Romley	661-343-3218	
City of LA	Steve Pedersen	213-725-6308	
NRC ES	Michael Sica	310-628-0725	
NRC ES	Jim Kiatos	310-628-1211	
4. Prepared by: (Con S. Garcia	mmunications Unit)	Date / Tin 02/09/11	
	ONS LIST		ICS 205a-CG (Rev. 07/04)





	ICS KEY PERSONNEL - NRCES	
Project Manager	Mike Sica	310-628-0725
Project Supervisor	Jim Kiatos	310-628-1211
Regional Health & Safety Mgr	Aimee Wilson	310-629-1190
Safety Director	Mike Amen, CIH, CSP, CHMM	503-978-7297

Date: 1.17.11 Start Time: 0700 Job Number: 56448 □ Land Emergency Response □ Marine Emergency Response □: Land Service □ Marine Service This site specific health and safety plan has been developed to provide a safe work environment for the SITE contracted work to be performed at Leeds Avenue near the intersection with Grant Street in Wilmington, **DESCRIPTION** California. Site Orientation prior to work assignment (layout, ingress; egress; emergency eyac, phones) Preventive booming: containment of liquids on the surface of the water to prevent migration into open water **SCOPE OF** Continue recovery of surface product Follow waste segregation & recovery plan and keep separate from other wastes WORK Maintain established temporary sand bag containment pond Continue skimming and recovery efforts to minimize downstream impacts to pump station Assess cleanup issues to implement once source has been isolated Pickup truck **EQUIPMENT** Gear truck Generator Weir skimmer Air compressor 3" pump & hoses Light tower 4" trash pump

**CHEMICAL INFORMATION (see MSDS)** 

Baker tanks Vacuum trucks

Rocket launcher Roll off bins

Emergency response trailer

Combustible gas indicator (4 gas meter) w/ PID

CHEMICAL / CAS	CHEMICAL PROPERTIES	EXPOSURE LIMITS	ROUTES OF ENTRY	SYMPTOMS
Crude Oil (sour)	<ul> <li>VD = 3 - 5</li> <li>VP = variable</li> <li>S.G. = AP 0.7 to 0.9</li> <li>FP = &lt;73 to &gt;200 F</li> </ul>	PEL: 5 mg/m³ as mineral oil mist	Inhalation Ingestion	Eye, nose and throat irritation, vertigo, nausea, dyspnea, central
Benzene	S.G. = 0.88 VP = 75mmHg FP = 12 F LEL: 1.2% UEL = 7.8%	PEL: 1 ppm IDLH: 500ppm	Contact Inhalation Ingestion Absorption	Irrit eyes, skin, nose, resp sys; dizz; head, nau, staggered gait; anor, lass; derm; bone marrow depress;
Hydrogen Sulfide	☐ MW = 34.1 ☐ Sol = 0.4% ☐ IP 10.4 6eV ☐ UEL = 44% ☐ LEL = 4.0%	PEL: 20 ppm IDLH: 100ppm	☐ Inhalation ☐ Contact	Irrit eyes, resp sys; apnea, coma, convuls; conj, eye pain, lac, photo; dizz, head





# PERSONAL PROTECTIVE EQUIPMENT

TASK	Level	MASK /CARTRIDGE /AIR	ADDITIONAL PPE
Establish support area / prepare	D	N/A	Hardhats, safety glasses, nomex coveralls, tyvek coveralls, leather gloves, PVC steel toe boots
Preventive Booming	D	N/A	Hardhats, safety glasses, tyvek coveralls, leather gloves, PVC steel toe boots, PFD.
Operator – Vac Truck	D	N/A	Hardhats, full-face shields, safety glasses, hearing protection, coveralls, neoprene outer gloves, PVC steel toe boots, high visible traffic vests
Load / transport material	D	N/A	Hardhats, safety glasses, tyvek coveralls, nitrile liner gloves, steel toe boots, high visible traffic vests
Decontaminate equipment	D	N/A	Hardhats, full-face shields, safety glasses, poly coated tyvek coveralls, neoprene outer gloves, nitrile liner gloves, PVC steel toe boots
Confined Space Entrants – NOT ANTICIPATED AT THIS SITE	В	Full-face air positive pressure demand respirator	Hardhat, safety glasses, nomex coveralls, nitrile steel toe boots, nitrile liners, pvc gloves, full body harness, retrieval winch set up, safety/rescue line for winch retrieval

## **ACTIVITY HAZARD ANALYSIS**

Hazards Throughout the Job				
ITEM	HAZARD	PREVENTION		
General Work Area	Slip / trip / fall	<ul> <li>designated pathways cleared of debris</li> <li>use step ladders for platforms requiring climbing up or down</li> <li>see attached safety memo regarding climbing on ladders/equip</li> </ul>		
General Work Area -lifting	Strain	<ul> <li>plan and stage to minimize long distance carrying</li> <li>split heavy loads into smaller loads</li> <li>use assistant for heavy or awkward load</li> </ul>		
General Work Area –Traffic	Struck by	<ul><li>Set up visible barricades on access roads;</li><li>Wear high visibility safety vests</li></ul>		
Refueling Equipment	Fire Spill	<ul> <li>Flammable liquids in explosion proof containers</li> <li>No flammable liquids or gas stored in unmarked containers</li> <li>Fire extinguisher near refueling and storage areas</li> <li>Area in front of extinguishers kept clear</li> <li>Spill containment plan discussed and in place</li> </ul>		
Heat stress	Heavy PPE Lack of breeze	Drink plenty of fluids		
Traffic	Struck by	<ul> <li>Set up visible barricades</li> <li>Only authorized NRCES personnel in work zones</li> </ul>		

Hazards Unique to Each Phase of Project				
ITEM	HAZARD	PREVENTION		
Trains on active railway	Struck by train Uneven walking surface	<ul> <li>Must have flagger present at all times to grant access to walk near railway</li> <li>Reflective orange safety vests must be worn</li> <li>Must maintain a minimum distance of 25' from track</li> <li>Use caution while walking on rocky surface</li> <li>Ensure steel toe boots are laced up and secure on ankle</li> </ul>		
Load containment materials	Material	plan and stage to minimize long distance lifting /carrying		

Site Specific Safety Plan – Dominguez Channel Mystery Oil Spill – 01.17.11 Rev. 1





Hazards Unique to Each Phase of Project				
into drop boxes	handling	<ul> <li>split heavy loads into smaller loads</li> <li>use mechanical lifting aids when possible</li> <li>have assistant for heavy or awkward loads</li> </ul>		
Transport absorbent boom materials to and from work sites	Lifting Strain	<ul> <li>Do not fill bags completely full</li> <li>buddy system for awkward loads</li> </ul>		
FLAMMABLE LIQUIDS	Smoking/ignit ion source	Post NO SMOKING signs around spill site/keep public out of work zone		
Low visibility	No sunlight	<ul><li>Set up light towers</li><li>Use head lamps on hard hats if needed</li></ul>		
Liquid Pumping / agitation Into vacuum truck	Static Contact Liquid Spill	<ul> <li>Bond and ground vacuum truck</li> <li>Bond and ground tank during cleaning / pumping</li> <li>Intrinsically safe equipment</li> <li>Spill containment plan discussed and in place during all cleaning operations</li> <li>Operator present at all times</li> </ul>		
Air monitoring	Inhalation Over exposure	<ul> <li>Ensure current calibration</li> <li>Fresh air calibration</li> <li>Bump test</li> <li>MUST have (1) 4 gas meter per group in skiffs/vessels</li> </ul>		
Confined Space – NOT ANTICIPATED AT THIS SITE	Atmosphere Rescue Ventilation	NRCES confined space permit for each entry. NRCES rescue /retrieval equipment in Safety Required Sec.  Note that this is horizontal rescue so may require wrist bands also		
Confined Space Entry - NOT ANTICIPATED AT THIS SITE	Hazardous Atmosphere	<ul> <li>A confined space permit will be filled out by the supervisor prior to each entry at a new location.</li> <li>Pre-entry air monitoring will be conducted to confirm a non-hazardous atmosphere.</li> </ul>		
	Slips Trips Falls	<ul> <li>Continuous air monitoring will be conducted by the hole watch and documented on NRCES' air monitoring log</li> <li>Forced air ventilation will be maintained</li> <li>All vertical entries will be made with the use of a winch and attendant.</li> </ul>		
	Illumination	<ul> <li>Three Points of contacts at all times when ascending or descending ladders</li> <li>Lower and raise equipment in buckets / ropes</li> </ul>		
	Opening of manhole	<ul> <li>Any employee who participates in confined space entry has been trained in accordance with 29 CFR 1910.146 and 8 CCR 515.</li> <li>Good housekeeping practices will be maintained during entry. Ensure there are not any items sitting below the ladder that could pose a tripping hazard.</li> <li>Intrinsically safe flash lights &amp; lights will be used to increase visibility in confined spaces</li> </ul>		
		<ul> <li>When opening is removed, a "hole watch" will be posted at that position until the cover is replaced.</li> <li>Prior to entry, the confined space supervisor will fill out the confined space permit.</li> </ul>		

# **SAFETY EQUIPMENT REQUIRED:**

<b>✓</b>	Eyewash / Shower	1	Decon Pool / Supplies	1	Wheel chocks for trucks
1	First Aid Kit	✓	Fire Extinguisher (A/B/C)	1	4 Way air monitoring instrument
1	Reflective orange vest	✓	Barricades / rope	1	Ladder

# TRAINING REQUIREMENTS:

1	HAZWOPER 40 / 24	✓	Hazwoper Supervisor	✓	Current 8 Hour Refresher
1	First Aid /CPR	✓	Hazard Communication	✓	Incident Command System





#### **DECONTAMINATION AND DISPOSAL**

DECONTAMINAT	ION EQUIPMENT			
$oxed{igspace}$ Visqueen ( Ground)	$oxed{\boxtimes}$ Rags to wipe boot bottoms			
igtimes Carpet Strips ( Ground)	☐ Labeled Drums for disposal items			
igert Decon Pool / wash boots	Chairs to sit on for PPE removal			
	Soap /Water to wash face / hands			
	Disposable Paper Towels			
	☐ Caution tape to designate decon area			
PERSONNEL DECON	ITAMINATION PLAN			
<ul> <li>Establish three stage contamination reduction zone with</li> </ul>	small decon area at exit			
☐ Lay down visqueen under barrier	Lay down visqueen under barrier			
Place empty lined and labeled drums for contaminated PPE				
□ Untape gloves and boots				
☐ Rinse boots if not using boot covers				
☐ Sit on chair prior to removing boots or outer PPE				
☐ Remove boots and outer gloves ;				
dispose of tape / boots / gloves in labeled drum				
Unzip suit / pull off hood (if hooded)				
☐ Roll down suit / inside out and place into labeled contain	er: DO NOT USE KNIVES TO CUT OFF PPE			
Remove inner gloves				
PPE and debris will be bagged, accounted for, and bulked	d into the applicable waste bin			





#### **EMERGENCY MEDICAL TREATMENT AND FIRST AID**

TYPE CONTACT	FIRST AID
Eyes	<ul> <li>Flush each eyes continuously for 15 minutes;</li> <li>Tilt head to side to ensure liquid runs onto floor not other eye</li> <li>refer to EMT for evaluation</li> </ul>
Skin	<ul> <li>Remove contaminated clothing immediately</li> <li>Wash skin continuously for 15 minutes;</li> <li>refer to physician if redness, swelling, or pain persists after washing</li> </ul>
Breathing	<ul> <li>Call 911;</li> <li>Remove to fresh air immediately;</li> <li>begin CPR until EMT arrives</li> </ul>
Ingestion	<ul> <li>aspiration hazard</li> <li>do not induce vomiting</li> <li>do not give anything by mouth</li> </ul>

# **EMERGENCY RESPONSE PLAN Attach Map to Nearest Hospital**

ELEMENT	LOCATION, SPECIFICATION OR REASON FOR USE		
NEAREST HOSPITAL	Pacific Hospital of Long Beach 2776 E Pacific Ave. Long Beach, CA 90806		
NEAREST PHONE	Supervisor cell phone		
FIRST AID KIT	Supervisor Truck		
FIRE EXTINGUISHER	Supervisor truck and charged extinguishers on site		
EYEWASH STATION AND EMERGENCY SHOWER	Supervisor will determine location on site or provide 55 gallon drum of water and hand pump		
EVACUATION ROUTE / MEETING POINT	To be discussed and diagramed before start of job scope		

**ACCIDENT / INCIDENT REPORTING** 

NRCES Notification Requirements			
FIRST AID INJURIES REQUIRING MEDICAL TREATMENT VEHICLE ACCIDENT NEAR MISS	<ul> <li>Employees immediately report all accidents or incidents to the Site Project Manager / Safety Officer</li> <li>Site Project Supervisor will immediately notify the NRCES Project Manager via cell phone.</li> <li>If unable to reach the Project Manager, contact the NRCES Operations or NRCES Safety Manager.</li> <li>Call their cell phones</li> <li>Safety Manager will provide employee disposition guidelines and coordinate an accident investigation either by himself or Project Supervisor</li> <li>NRCES Project Manager will relay information to Project Site Superintendent</li> <li>Accident reporting forms are available electronically</li> <li>Report all incidents to NRCES Safety Director</li> <li>Ensure incident documented on Daily Safety Meeting Form</li> <li>Determination will be made regarding need for post accident drug testing</li> </ul>		





#### **SAFETY PLAN APPROVAL**

Site Safety Officer	Date
---------------------	------

#### **ACKNOWLEDGMENTS**

I have read and understand the topics outlined on all pages of this HASP and will follow all the required safety rules.

\*\*I am aware that I am to sign In at the beginning of the shift and sign out at the end of my shift on the daily safety meeting form.

I must notify the on site supervisor of any injury /accident/ near miss that I had or observed during my shift\*\*

I understand that I have the right to stop work and report any potential hazards to the NRCES Site Supervisor.

After an injury/accident/near miss is reported, the Site Supervisor must call the H & S Manager at 310-629-1190.


Date	Print Name	Signature
× ·		
÷		
i sr		
	·	





# **ATTACHMENT B**

# **Medical Facilities**



1926 E Pacific Coast Hwy, Los Angeles, CA 90744	
1. Head east on CA-1 S About 2 mins	go 1.7 mi total 1.7 mi
2. Slight right to merge onto I-710 N toward Pasadena About 1 min	go 1.0 mi total 2.7 mi
3. Take exit 3A for Willow St E	go 0.2 mi total 3.0 mi
Merge onto W Willow St     About 2 mins	go 0.7 mi total 3.7 mi
5. Turn left at Pacific Ave Destination will be on the right About 1 min	go 9.2 mi total 3.9 mi
B 2776 Pacific Ave, Long Beach, CA 90806	





# ATTACHMENT A MATERIAL SAFETY DATA SHEETS

**Crude Oil (Sour)** 



#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

1. CHEMICAL PRODUCT and COMPANY INFORMATION

(rev. Jan-99)

Amerada Hess Corporation 1 Hess Plaza

Woodbridge, NJ 07095-0961

EMERGENCY TELEPHONE NUMBER (24 hrs):

CHEMTREC

(800) 424-9300

COMPANY CONTACT (business hours):

Corporate Safety

(732) 750-6000

**SYNONYMS**: Crude Petroleum; Sour Crude See Section 16 for abbreviations and acronyms.

#### 2. COMPOSITION and INFORMATION ON INGREDIENTS

(rev. Jan-99)

CONCENTRATION PERCENT BY WEIGHT INGREDIENT NAME **EXPOSURE LIMITS** OSHA PEL-TWA: 5 mg/m³ as mineral oil mist ACGIH TLV-TWA: 5 mg/m³ as mineral oil mist\* Petroleum Oil 100 CAS NUMBER: 8002-05-9 \*1997 NOIC: sum of 15 NTP-listed polynuclear aromatic hydrocarbons 0.005 mg/m<sup>3</sup>, A1 OSHA PEL-Ceiling/Peak: 20 / 50 ppm < highly variable - see Hydrogen Sulfide (H<sub>2</sub>S) ACGIH TLV-TWA/STEL: 10 / 15 ppm below > CAS NUMBER: 7783-06-4 OSHA PEL-TWA/STEL: 1/5 ppm Variable Renzene 0.5 / 2.5 ppm, ACGIH TLV-TWA: AP 0.1 to 1.0 CAS NUMBER: 71-43-2 A1, skin

US Coast Guard: same as OSHA
A natural product derived from various oil production field primarily consisting of a complex combination of paraffinic and aromatic hydrocarbons and small amounts of nitrogen and sulfur compounds.

Crude oils are generally referred to as "sour" if they can release dissolved hydrogen sulfide ( $H_2S$ ) which could result in a hazardous condition. The amount of dissolved  $H_2S$  can vary considerably with the crude oil source. Some sour crude oils can have an appreciable percentage of  $H_2S$ .

#### 3. HAZARDS IDENTIFICATION

(rev. Jan-99; Tox 99)

# EMERGENCY OVERVIEW CAUTION!

FLAMMABLE LIQUID - MAY EVOLVE TOXIC AND FLAMMABLE HYDROGEN SULFIDE GAS - SLIGHT TO MODERATE IRRITANT - EFFECTS CENTRAL NERVOUS SYSTEM - HARMFUL OR FATAL IF SWALLOWED

High fire hazard. Keep away from heat, spark, open flame, and other ignition sources.

HYDROGEN SULFIDE (toxic gas) may be released. High concentration may cause immediate unconsciousness - death may result unless victim is promptly and successfully resuscitated. Hydrogen sulfide causes eye irritation.

If ingested, do NOT induce vomiting, as this may cause chemical pneumonia (fluid in the lungs). Contact may cause eye, skin and mucous membrane irritation. Avoid prolonged breathing of vapors or mists. Inhalation may cause irritation, anesthetic effects (dizziness, nausea, headache, intoxication), and respiratory system effects.

Long-term exposure may cause effects to specific organs, such as to the liver, kidneys, blood, nervous system, and skin. Contains benzene, which can cause blood disease, including anemia and leukemia.

#### **EYES**

Contact with eyes may cause moderate to severe irritation.

Revision Date: 02/24/00 Page 1 of 8

#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

#### SKIN

Practically non-toxic if absorbed following acute (single) exposure. May cause skin irritation with prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly. Rare, precancerous warts on the forearms, backs of hands and scrotum have been reported from prolonged or repeated skin contact.

#### INGESTION

The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest, and death may occur.

#### INHALATION

Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system (brain) effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

**WARNING**: Irritating and toxic hydrogen sulfide gas may be found in confined vapor spaces. Greater than 15 - 20 ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50 - 500 ppm can cause headache, nausea, and dizziness, loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500 ppm can cause rapid or immediate unconsciousness due to respiratory paralysis and death by suffocation unless the victim is removed from exposure and successfully resuscitated.

The "rotten egg" odor of hydrogen sulfide is not a reliable indicator for warning of exposure, since olfactory fatigue (loss of smell) readily occurs, especially at concentrations above 50 ppm. At high concentrations, the victim may not even recognize the odor before becoming unconscious.

#### CHRONIC and CARCINOGENICITY

Similar products produced skin cancer and systemic toxicity in laboratory animals following repeated applications. This product contains polynuclear aromatic hydrocarbons which have been shown to be carcinogenic in laboratory animals after repeated and prolonged skin contact. The significance of these results to human exposures has not been determined - see Section 11, Toxicological Information.

Contains benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis (rash). Pre-existing, chronic respiratory disease, liver or kidney dysfunction, or central nervous system disorders may be aggravated by exposure.

#### 4. FIRST AID MEASURES

(rev. Jan-99; Tox-99)

#### **EYES**

In case of contact with eyes, immediately flush with clean, low-pressure water for at least 15 min. Hold eyelids open to ensure adequate flushing. Seek medical attention.

#### SKIN

Remove contaminated clothing. Wash contaminated areas thoroughly with soap and water or waterless hand cleanser. Obtain medical attention if irritation or redness develops. Thermal burns require immediate medical attention depending on the severity and the area of the body burned.

Revision Date: 02/24/00 Page 2 of 8

#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

#### INGESTION

DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Small amounts of material which enter the mouth should be rinsed out until the taste is dissipated.

Remove person to fresh air. If person is not breathing provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

#### FIRE FIGHTING MEASURES (rev. Oct-94)

#### FLAMMABLE PROPERTIES:

FLASH POINT:

< 73 to > 200 °F (< 23 to > 93 °C)

**AUTOIGNITION TEMPERATURE:** 

N/D

OSHA/NFPA FLAMMABILITY CLASS:

1B (flammable liquid)

LOWER EXPLOSIVE LIMIT (%):

N/D

UPPER EXPLOSIVE LIMIT (%):

N/D

#### FIRE AND EXPLOSION HAZARDS

Flash point and explosive limits are highly dependent on the crude oil source. Treat as an OSHA/NFPA flammable liquid unless otherwise indicated. Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

#### EXTINGUISHING MEDIA

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO2, water spray, fire fighting foam, or Halon.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

#### FIRE FIGHTING INSTRUCTIONS

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment.

Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing.

Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

See Section 16 for the NFPA 704 Hazard Rating.

#### 6. **ACCIDENTAL RELEASE MEASURES** (rev. Jan-99)

ACTIVATE FACILITY'S SPILL CONTINGENCY OR EMERGENCY RESPONSE PLAN.

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Hydrogen sulfide may be evolved during a release - ensure response personnel are adequately protected - see Section 8.

Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system

Revision Date: 02/24/00 Page 3 of 8

#### MATERIAL SAFETY DATA SHEET

## Crude Oil (Sour)

MSDS No. 6608

is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors.

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal. Response and clean-up crews must be properly trained and must utilize proper protective equipment.

#### 7. HANDLING and STORAGE

(rev. Jan-99)

#### HANDLING PRECAUTIONS

Handle as a flammable liquid. Keep away from heat, sparks, and open flame! Electrical equipment should be approved for classified area. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

#### STORAGE PRECAUTIONS

Keep away from flame, sparks, excessive temperatures and open flame. Use approved vented containers. Keep containers closed and clearly labeled. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition.

Store in a well-ventilated area. This storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". Avoid storage near incompatible materials. The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks".

Hydrogen sulfide may accumulate in tanks and bulk transport compartments. Consider appropriate respiratory protection (see Section 8). Stand upwind. Avoid vapors when opening hatches and dome covers. Confined spaces should be ventilated prior to entry.

#### WORK/HYGIENIC PRACTICES

Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use gasoline or solvents (naphtha, kerosene, etc.) for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.

#### Naturally Occurring Radioactive Materials (NORM):

Industry experience indicates that this material may contain small amounts of naturally-occurring uranium, thorium, and their decay products (NORM) which can accumulate in oil production and process equipment, particularly the equipment handling the water associated with crude oil production. Scales, other deposits, and sludges from this equipment may have a significant accumulation of NORM. Gamma radiation above background may be detected external to equipment contaminated with NORM. Production equipment should be assessed for external gamma radiation; access may need to be restricted in accordance with OSHA 29 CFR 1910.96 during operation. Such equipment should also be assumed to be internally contaminated with long half-life decay products that emit alpha radiation, which is a hazard if inhaled or ingested. Unless measurements indicate otherwise, steps should be taken to minimize skin and inhalation exposure to NORM dusts/mists by wearing personal protective clothing [such as disposable Tyvek ® (DuPont)], utilizing respiratory protection (minimum of HEPA filter), and practicing good personal hygiene. Please refer to API Bulletin E2, "Bulletin on Management of Naturally Occurring Radioactive Materials in Oil and Gas Production," April 1, 1992, for additional information on managing NORM.

#### 8. EXPOSURE CONTROLS and PERSONAL PROTECTION

(rev. Jan-99)

#### **ENGINEERING CONTROLS**

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.

Revision Date: 02/24/00 Page 4 of 8

#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

Page 5 of 8

#### EYE/FACE PROTECTION

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying

#### SKIN PROTECTION

Gloves constructed of nitrile, neoprene, or PVC are recommended. Chemical protective clothing such as of E.I. DuPont Tyvek QC®, Saranex®, TyChem® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information

#### RESPIRATORY PROTECTION

If a hydrogen sulfide hazard is present (that is, exposure potential above H<sub>2</sub>S permissible exposure limit), use a positive-pressure SCBA or Type C supplied air respirator with escape bottle.

Where it has been determined that there is no hydrogen sulfide exposure hazard (that is, exposure potential below H<sub>2</sub>S permissible exposure limit), a NIOSH/ MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection

Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

#### 9. PHYSICAL and CHEMICAL PROPERTIES (rev. Oct-94)

Variable depending on its source; typical is a thick, dark yellow to brown or greenish black liquid

#### **ODOR**

A characteristic, petroleum/asphalt-type odor

Hydrogen sulfide (H<sub>2</sub>S) has a rotten egg "sulfurous" odor. This odor should not be used as a warning property of toxic levels because H<sub>2</sub>S can overwhelm and deaden the sense of smell. Also, the odor of H<sub>2</sub>S in heavy oils can easily be masked by the petroleum-like odor of the oil. Therefore, the smell of H<sub>2</sub>S should not be used as an indicator of a hazardous condition - a H<sub>2</sub>S meter or colorimetric indicating tubes are typically used to determine the concentration of H2S.

#### BASIC PHYSICAL PROPERTIES

The properties of crude oil are highly variable depending on its source.

**BOILING RANGE:** 

AP 100 - 1000+ °F (> 260 °C)

VAPOR PRESSURE:

Variable

VAPOR DENSITY (air = 1):

3 - 5 typical

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): AP 0.7 to 0.9 (varies)

Variable

PERCENT VOLATILES:

**EVAPORATION RATE:** 

Variable

SOLUBILITY (H2O):

Insoluble to slightly soluble

#### STABILITY and REACTIVITY

(rev. Oct-94)

STABILITY: Stable. Hazardous polymerization will not occur.

#### CONDITIONS TO AVOID and INCOMPATIBLE MATERIALS

Material is stable under normal conditions. Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. Keep away from strong oxidizers.

#### **HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

TOXICOLOGICAL PROPERTIES 11.

(rev. Jan-99; Tox-99)

CHRONIC EFFECTS AND CARCINOGENICITY

Carcinogenicity: OSHA: NO IARC: NO NTP: NO

ACGIH: 1997 NOIC: A1

Dermal carcinogenicity: positive - mice

Studies have shown that similar products produce skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation.

This product contains benzene. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood-forming system (particularly bone marrow), and serious blood disorders such as aplastic anemia and leukemia. Benzene is listed as a human carcinogen by the NTP, IARC, OSHA and ACGIH.

#### **MUTAGENICITY** (genetic effects)

Some crude oils and crude oil fractions have been positive in mutagenicity studies.

**ECOLOGICAL INFORMATION** 

(rev. Jan-99)

Keep out of sewers, drainage and waterways. Report spills and releases, as applicable, under Federal and State regulations.

DISPOSAL CONSIDERATIONS

(rev. Jan-99)

Consult federal, state and local waste regulations to determine appropriate disposal options.

TRANSPORTATION INFORMATION

(rev. Jan-99)

PROPER SHIPPING NAME:

PETROLEUM CRUDE OIL

HAZARD CLASS; PACKING GROUP:

3; determine flash point to accurately classify packing group

DOT IDENTIFICATION NUMBER:

**UN 1267** FLAMMABLE LIQUID

DOT SHIPPING LABEL:

15.

REGULATORY INFORMATION

(rev. Jan-99)

## U.S. FEDERAL, STATE and LOCAL REGULATORY INFORMATION

This product and its constituents listed herein are on the EPA TSCA Inventory. Any spill or uncontrolled release of this product, including any substantial threat of release, may be subject to federal, state and/or local reporting requirements. This product and/or its constituents may also be subject to other regulations at the state and/or local level. Consult those regulations applicable to your facility/operation.

#### CLEAN WATER ACT (OIL SPILLS)

Any spill or release of this product to "navigable waters" (essentially any surface water, including certain wetlands) or adjoining shorelines sufficient to cause a visible sheen or deposit of a sludge or emulsion must be reported immediately to the National Response Center (1-800-424-8802) or, if not practical, the U.S. Coast Guard with follow-up to the National Response Center, as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies as required.

#### CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT)

The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts crude oil, refined, and unrefined petroleum products and any indigenous components of such. However, other federal reporting requirements (e.g., SARA Section 304 as well as the Clean Water Act if the spill occurs on navigable waters) may still apply.

SARA SECTION 311/312 - HAZARD CLASSES

ACUTE HEALTH X

CHRONIC HEALTH X

FIRE X

SUDDEN RELEASE OF PRESSURE

REACTIVE

#### MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

#### SARA SECTION 313 - SUPPLIER NOT IFICATION

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372:

INGREDIENT NAME (CAS NUMBER)

CONCENTRATION WT. PERCENT

Benzene (71-43-2)

0.1 to 1.0

CANADIAN REGULATORY INFORMATION (WHMIS)

Class B, Division 2 (flammable liquid)

Class D, Division 1A (Very toxic, acute)

Class D. Division 1B (Very toxic by other means)

OTHER INFORMATION 16.

(rev. Feb-00)

NFPA® HAZARD RATING

HEALTH:

2 Moderate

FIRE:

3 High

REACTIVITY:

0 Negligible

HMIS® HAZARD RATING

HEALTH:

3\* High 3

FIRE:

High

REACTIVITY:

Negligible

\*Chronic

SPECIAL HAZARDS: May release toxic hydrogen sulfide (poison gas).

SUPERSEDES MSDS DATED: 01/27/99

Industrial Hygienists

**ABBREVIATIONS:** 

AP = Approximately

< = Less than

> = Greater than

OPA

PEL

**OSHA** 

0

N/A = Not Applicable

N/D = Not Determined ppm = parts per million

ACRONYMS: American Conference of Governmental

ACGIH

**MSHA** 

NTP

AlHA American Industrial Hygiene Association	1
ANSI American National Standards Institute	
(212) 642-4900	
API American Petroleum Institute	
(202) 682-8000	
CERCLA Comprehensive Emergency Response,	
Compensation, and Liability Act	
DOT U.S. Department of Transportation	

Resource Conservation and Recovery **RCRA** REL Recommended Exposure Limit (NIOSH) SARA Superfund Amendments and

[General Info: (800)467-49221

Mine Safety and Health Administration

Reauthorization Act of 1986 Title III Self-Contained Breathing Apparatus SCBA

Oil Pollution Act of 1990

Administration

U.S. Occupational Safety & Health

Permissible Exposure Limit (OSHA)

U.S. Environmental Protection Agency FPA Hazardous Materials Information System **HMIS** 

SPCC -Spill Prevention, Control, and Countermeasures

**IARC** International Agency For Research On Cancer

STEL Short-Term Exposure Limit (generally 15 minutes)

National Fire Protection Association (617) **NFPA** 770-3000

TLV Threshold Limit Value (ACGIH) TSCA Toxic Substances Control Act Time Weighted Average (8 hr.) TWA Workplace Environmental Exposure WEEL

National Institute of Occupational Safety NIOSH and Health

Level (AlHA) Canadian Workplace Hazardous WHMIS

NOIC Notice of Intended Change (proposed Materials Information System

change to ACGIH TLV) National Toxicology Program

# MATERIAL SAFETY DATA SHEET

Crude Oil (Sour)

MSDS No. 6608

#### DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.